



# model 6518.2FR

Faucets and Valves

## FEATURES & BENEFITS

### SERVICEABILITY

Operation and maintenance ease is achieved through both the automatic stream regulation and the ability of the valve assembly to be lifted to the surface and lowered back into the casing, so in the rare event that maintenance is required, can be done without having to disturb the fountain.

### YEAR-ROUND SERVICE

Reliable and fully engineered system allows for two pneumatic valves to be installed below the frost line, and equipped with the ability to drain the water line after use to non-freezing depths so the unit can be used year round.

## OPTIONS

- ❑ Discontinued Drinking Fountains: Model 6625, ground box with lid, used with freeze-resistant valve models 6518FR and 6518.2FR.

To see all options for this model, visit [www.hawasco.com](http://www.hawasco.com)



## SPECIFICATIONS

Model 6518.2FR freeze-resistant bury valve for use with dual bubbler head pedestal fountains shall include dual brass pneumatic operated valves installed below the frost line, check valve to drain water from unit when not in use and to prevent back-flow cross contamination, self-regulating .4 gpm flow controls, separate valve access and pull-out design for easy maintenance, 6" diameter PVC pipe to encase valve assembly, and 1/2" IPS supply.

## APPLICATIONS

Freeze-resistant valve system is used with all Haws "Hi-Lo" two bubbler, freeze-resistant, pedestal mounted fountains. Because this valve is installed below the frost line, it allows the fountain it is installed with to function year round in freezing conditions. Responsible for this non-freezing feat are two pneumatic operated valves that drain the water from the fountains to non-freezing depths. Product is compliant to California Health and Safety Code 116875 (AB 1953-2006).

