

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The PK3 parka features a comfortable 88% cotton 12% Nylon twill material with a modacrylic quilted lining for warmth and protection. Max Comfort™ material meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Gray and Navy.

FEATURES:

- Max Comfort™ Fabric NFPA 2112 UL Certified
- All Trims are NFPA 2112 UL Certified
- NFPA 70E Hazard/Risk Cat HRC3
- ASTM F1506 Electric Arc Protection Standard
- ATPV ASTM 1959 35 cal/cm², HRC 3
- Parka is UL & NFPA 2112 Certified
- **Max Comfort™ 7.5 oz. 88% Cotton/12% Nylon Outer Shell**
- **11.5 oz. quilted lining – 100% FR treated cotton and non-woven modacrylic batting**
- Water Repellent
- Sewn with FR Aramid thread
- Double needle stitching on main seams
- 2 Double entry hand pockets with snap closed flap top entry and side entry pockets
- Pleated action back provides arms with 360 degree full range of motion
- FR Knit inside storm cuff at hem of sleeves provides comfort and maintain heat
- Pencil stall on left sleeve
- Protective storm flap covers 2-way #10 brass separating front zipper
- Inside chest pocket
- Adjustable drawcord in waist with FR heat resistant grippers
- Double snap closure at neck – Wrap for protection and warmth
- Covered snaps for electric-arc protection
- Two patch pockets on chest with hidden snap closures





MCR
SAFETY

PK3G

Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Utilities, Fracking, Electronic Assembly,
Mining

TECHNICAL DATA FOR: PK3G

Brand	MCR Safety FR Gear	Front Closure	Zipper & Snaps
Series	Max Comfort	NFPA 2112 Cert.	Yes
Size	L	NFPA 70E Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	ASTM 1930 Cert.	Yes
Material Weight	7.5 oz.	ASTM F1506 Cert.	Yes
Flame Resistant	Flame Resistant	Hazard Risk Category	HRC3

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
PK3GLT	44-46	N/A	N/A	N/A	N/A	N/A	35.940
PK3GL	44-46	N/A	N/A	N/A	N/A	N/A	33.024
PK3GM	40-42	N/A	N/A	N/A	N/A	N/A	31.848
PK3GS	36-38	N/A	N/A	N/A	N/A	N/A	30.680
PK3GX2	52-54	N/A	N/A	N/A	N/A	N/A	36.152
PK3GX2T	52-54	N/A	N/A	N/A	N/A	N/A	37.304
PK3GX3T	56-58	N/A	N/A	N/A	N/A	N/A	39.040
PK3GX3	56-58	N/A	N/A	N/A	N/A	N/A	38.592
PK3GX4	60-62	N/A	N/A	N/A	N/A	N/A	40.888
PK3GX4T	60-62	N/A	N/A	N/A	N/A	N/A	41.152
PK3GX5T	64-66	N/A	N/A	N/A	N/A	N/A	42.512
PK3GX5	64-66	N/A	N/A	N/A	N/A	N/A	43.032
PK3GXL	48-50	N/A	N/A	N/A	N/A	N/A	34.328
PK3GXLT	48-50	N/A	N/A	N/A	N/A	N/A	34.680

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2016 MCR Safety - All Rights Reserved