



# SPECIFICATION SHEET

## 19-D350



### G-TEK® 3GX, 13 GAUGE DYNEEMA® DIAMOND BLENDED SHELL WITH FOAM NITRILE COATED PALM

- Washable, resistant to chemicals, water and ultraviolet light.
- Seamless construction
- Foam Nitrile coated palm and knuckles are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Dyneema® Diamond blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Cotton color binding denotes sizing

### APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- Parts assembly
- Sharp small parts handling
- Construction
- Other general duty applications

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

### TECHNICAL DATA

|             |                                            |                    |                    |                  |
|-------------|--------------------------------------------|--------------------|--------------------|------------------|
| MATERIAL    | Shell: Dyneema® Diamond / Coating: Nitrile |                    |                    |                  |
| COLOR       | Shell: ■ Salt & Pepper / Coating: ■ Black  |                    |                    |                  |
| CUFF STYLE  | Continuous Knit                            |                    |                    |                  |
| SIZES       | S - XL                                     |                    |                    |                  |
| PACKAGING   | 12 pairs per dozen, 6 dozen per case       |                    |                    |                  |
| CASE        | 11.8" x 12.6" x 14.2" / 30cm x 32cm x 36cm |                    |                    |                  |
| CASE WEIGHT | S                                          | M                  | L                  | XL               |
|             | 11.5 lbs<br>5.2 kg                         | 12.3 lbs<br>5.6 kg | 12.6 lbs<br>5.7 kg | 13.2 lbs<br>6 kg |
| COO         | China                                      |                    |                    |                  |

### PERFORMANCE PROPERTIES

|             |                  |   |   |   |   |   |
|-------------|------------------|---|---|---|---|---|
| EN388: 4342 | ANSI Cut Level 2 |   |   |   |   |   |
| ABRASION    | 0                | 1 | 2 | 3 | 4 | 5 |
| CUT         | 0                | 1 | 2 | 3 | 4 | 5 |
| TEAR        | 0                | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE    | 0                | 1 | 2 | 3 | 4 | 5 |

### BARCODES

| ITEM         | BAG          | DOZEN          | CASE           |
|--------------|--------------|----------------|----------------|
| ■ 19-D350/S  | 616314167836 | 01616314167835 | 02616314167834 |
| ■ 19-D350/M  | 616314167829 | 01616314167828 | 02616314167827 |
| ■ 19-D350/L  | 616314167812 | 01616314167811 | 02616314167810 |
| ■ 19-D350/XL | 616314167843 | 01616314167842 | 02616314167841 |



### DIMENSIONS (in/cm)

|   | S         | M          | L        | XL         |
|---|-----------|------------|----------|------------|
| A | 9.1 / 23  | 9.4 / 24   | 9.8 / 25 | 10.2 / 26  |
| B | 3.7 / 9.5 | 4.1 / 10.5 | 4.3 / 11 | 4.5 / 11.5 |
| H | Red       | Yellow     | Brown    | Black      |

