



ECONO-MARK

An economically priced marking paint that has a water base formulation which results in a highly visible permanent mark. Special spray head for writing, spot marking or line marking.

Suggested Uses:

Forestry
Petrochemical
Mining
Lumber
Screen enclosures

Benefits:

Economical
Narrow concentrated spray
Produces vivid marks
V.O.C. Compliant
Long lasting
Lower Flammability
Non-clogging

Packaging:

Cans per case	12
Shipping weight per case	12 lbs.
Container	16 fluid ounce can
Label weight	11 ounces (312 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Flammable"
Flash point	-4F
Specific Gravity	0.80
Solids Content	~18%
VOC content	~56%, cannot exceed 60%
MIR value	~1.10, cannot exceed 1.20
HAPs content	19%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Good
Abrasion Resistance	Good
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To handle	45 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code
16-2002	White	043281001199
16-2003	Black	043281001205
16-2004	Red	043281001212
16-2034	Yellow	043281001229
16-2035	Blue	043281001236
16-2088	Green	043281001243