



SPECIAL FEATURES

- Sport styling with maximum protection
- Curved lens with side window gives fashionable look with panoramic view
- Durable frame gives a pressure free fit
- Soft nose piece and rubber insert temple tips provide a comfortable fit
- Scratch resistant lenses filter out 99.9% of harmful UV rays
- Exceeds ANSI Z87.1 – 2003 High Impact Requirements

GENERAL SPECIFICATIONS

- Lens thickness: 2.30 mm
- PD: 68 mm
- Lens Base: 8 curve
- Weight: 29 gm
- Lens size vertical: 44 mm
- Lens size diagonal: 70.8 mm
- Bridge: 13.4 mm
- Temple length (lens-tip): 157 mm
- Overall Width (hinge-hinge): 127.5 mm
- Closest point between lens: 14.8mm
- Closest point between temple tips: 93mm

FRAME & LENS OPTIONS

- Lens options:
 - o Clear, tinted, mirrored available for your selection
- Temple options
 - o Various

| COMPONENT | MATERIAL | FEATURES |
|------------------|-----------------|--|
| Lens | Polycarbonate | 8 base Curve, Wrap around design w/side protection |
| Side window lens | Polycarbonate | Along with the front lens makes full wrap around image |
| Frame | Nylon | Durable & flexible, sporty style |
| Nose piece | PVC | Universal |
| Temple | Nylon | Spatula |
| Temple tip | PVC | Comfortable & good for color variants |
| Hinge | Nylon | 3 Barrel Type, integral to Frame & temples |
| Screw | Stainless Steel | Standard Hinge screw |

MARKINGS

Lens: As per specification
Frame: As per specification

PACKAGING

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in an outer carton

STANDARDS

Meets ANSI Z87.1