



PMXTORQ®

SPECIAL FEATURES

- Attractive, modern half-frame design
- Ventilated nose piece allows heat to dissipate from nose bridge to reduce fogging
- Wide, straight back temples provide secure fit in all conditions.
- Innovative, streamline spectacle incorporates the elements of safety in trend setting eyewear.
- Scratch-resistant, polycarbonate lens provide 99.9% of UV protection

GENERAL SPECIFICATIONS

Lens thickness: 1.8 mm
 PD: 68mm
 Lens Base: 8 curve
 Weight: 33 gm
 Lens size vertical: 43mm
 Lens size diagonal: 70.5mm
 Bridge: 13mm
 Temple length(lens-tip): 175mm
 Overall Width(hinge-hinge): 131mm
 Closest point between lens: 15mm
 Closest point between temple tips: 98mm

FRAME & LENS OPTIONS

Frame colors: Various
 Lens options: Standard colors, special tint, or mirror lens available

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Polycarbonate	Lens clipped to frame
Nose piece	PVC	Universal fit
Temple	Polycarbonate	Soft tips for comfort
Temple tip	TPR	
Hinge	Polycarbonate	3 Barrel Type
Screw	Stainless Steel	Standard Hinge screw

MARKINGS

Lens: As per Specification
 Frame: As per Specification

PACKAGING

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in a case

STANDARDS

Meets ANSI, CE, AS and CSA