



XSG™

SPECIAL FEATURES:

- Flame resistant foam padding forms a seal to keep out dust and airborne particles.
- Lenses are treated to prevent fogging, scratching, and static.
- Interchangeable temples/strap included with each pair.
- Strap has Quick Fit retainer for easy on/off.
- Design allows air to flow freely reducing heat.
- XS EASE Replacement lens system.
- XSG™ Ballistic passes MIL-PRF-31013 Ballistic Standards and meets the ANSI Z87.1-2003 High Velocity Impact Standard.
- Lenses provide 99% protection against harmful UV rays.

GENERAL SPECIFICATIONS

Lens Thickness:	2.3mm	PD	68 mm
Lens Base	8.0 curve	Weight	35 gm
Lens size vertical	44mm	Lens Size Diagonal	66.3 mm
Bridge	13.7mm		
Overall length (lens-tip)	163mm	Over width	136.5mm
Closet point between lens	18.5mm	Closet point between temple tip	56mm
Strap length	420mm		

FRAME AND LENS OPTIONS:

Frame colors:	Black and various colors
Lens options:	Clear, tinted, and mirror lenses

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8.0 base dual lenses
Outer Frame/Sponge	Polycarbonate/EVA	Flexible fitting body with anti-flaming sponge
Inner frame	Nylon	Flexible fitting body with Dual lenses
Parts-1	Polycarbonate	Screwed in frame
Parts-2	Polycarbonate/PVC	Clip on Parts-1
Nose piece	EVA	Universal, integral to frame
Headband	Polyester	Adjustable textile elastic
		Fixed on clipping parts
Temple/tip	Polycarbonate/PVC	Clip on Parts-1
Screw	Stainless Steel	standard hinge screw

MARKINGS

PACKAGING

STANDARDS

MEETS ANSI Z87.1 STANDARDS TEST RESULTS AVAILABLE UPON REQUEST